



Axis-QRA 200

Wall-mounted axial fans with aluminium impellers

- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position


	Unit of measurement	Axis-QRA 200	
Phases	-	1	
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50	60
Maximum airflow	m³/h	390	
Weight	kg	2.5	
Transported air temperature (max)	°C	40	
Transported air temperature (min)	°C	-30	
Ingress protection rating	-	IP24	
Ingress protection rating of the drive	-	IP44	
Impeller material	-	Aluminium	



speed_1
80
60
40
20
0
Static pressure [Pa]
0
200
400
Airflow [m3/h]



Dimensions

ØD	ØD1	ØD2	Ød	L
208	270	300	7	120


ø d
L
ø D1
ø D2


ø D+10
ø D

Ecodesign

Trademark	Blauberg
Model	Axis-QRA 200
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	42
Maximum external leakage rates (%)	2.7
Static efficiency (%)	8.6
Declared typology	NRVU UVU
Effective electric power input (kW)	0.027
Sound power level (dB(A))	52

Accessories

Transformer speed controllers

Name	Photo	Description
CDR5E E3.5 TP		Single phase speed controller
CDR5E E5.0 TP		Single phase speed controller
CDR5E E7.5 TP		Single phase speed controller
CDR5E E1.5 TP		Single phase speed controller