

BL02 RH 2500

Floor mounted heat recovery units

• Heat exchanger type: Rotary, condensation or enthalpy
• Heat exchanger material: Aluminium/aluminium with hygroscopic coating
• Sound-insulated casing
• Reheater: Optional
• Preheater: Optional
• BMS protocol: Bacnet, ModBus
• Control: Wired control panel
• Casing material: Aluzinc steel

	Unit of measurement	BL02 RH 2500
Casing performance	-	40 mm, T3/TB4
Phases	-	3
Minimum supply voltage	V	380
Maximum supply voltage	V	400
Power supply frequency	Hz	50/60
Rated power supply fan	W	1200
Rated power extract fan	W	1200
Unit current (without electric heaters)	A	4.3
Maximum airflow	m^3/h	3050
Maximum airflow at ESP 200 Pa	m^3/h	2900
Heat exchanger type	-	Rotary, condensation or enthalpy
Heat exchanger material	-	Aluminium/aluminium with hygroscopic coating
Weight	kg	245
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature max	°C	60
Ambient air temperature min	°C	-40
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP54

Dimensions