

Cabrio Base V2 100 T

Innovative domestic exhaust fan with an automatic shutter and low noise operation

- Impeller type: Axial
- Casing material: Plastic
- Timer: Internal timer, Turn off timer, Turn on timer

	Unit of measurement	Cabrio Base V2 100 T	
Speed	-	1	2
Minimum supply voltage	V	220	
Maximum supply voltage	V	240	
Power supply frequency	Hz	50	
Maximum airflow	m³/h	60	90
Weight	kg	0.55	
Ambient air temperature min	°C	1	
Ambient air temperature max	°C	40	
Ingress protection rating	-	IP44	
Impeller material	-	Plastic	

Dimensions

a	b	c	Ø d	e
175	221	77	99	39


b
a
Ød
c
e

Ecodesign

Trademark	Blauberg					
Model	Cabrio Base V2 100 T					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-33.7	B	-15.8	E	-5.5	F
Type of ventilation unit	Unidirectional					
Type of drive installed	2-speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	90					
Electric power input (W)	8.5					
Reference flow rate (m³/s)	0.017					
Specific power input (SPI) (W/(m³/h))	0.1					
Control typology	Clock control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	42					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	118		118		118	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3667		1874		848	

Accessories

Speed control switches

Name	Photo	Description
CDP-2/5		Multi-speed switch
CDP-2/10		Multi-speed switch