





Select the unit online in a few clicks and get full technical data at blaubergselector.com

READING THE MODEL CODE



BLAUAIR RP

Ceiling mounted heat recovery units

Blauberg Ventilatoren GmbH
Aidenbachstr. 52
D-81379 Munich


info@blaubergventilatoren.de
www.blaubergventilatoren.de

Technical changes reserved.
Illustrations and texts are non-binding.

BLAUAIR RP

Premium range of ceiling mounted heat recovery units for commercial applications.

The unit is available in three sizes with rated air flow 800–2500 m³/h, with heaters and cooling coils.



FANS

EBM fans with EC motors. Impellers with backward-curved blades.

Low power consumption at any speed, low noise and stable operation in any climate.



CONTROLS

Integrated plug-and-play controls based on Carel kVent controller.



Easy connectivity via Web interface by Ethernet cable. Modbus and Bacnet protocols.



USER PANELS

S30 th-Tune: simple control panel ensures basic setting options with user-friendly interface.



S32 pGDe: extended control panel for full functionality engineering adjustment.



FRAMELESS CASING SYSTEM

Casing panels made of zinc -aluminum coated steel with a 40 mm mineral wool heat- and sound-insulating layer. Corrosion class C4 according to ISO 12944: class C4. Each model available in left or right versions. Service access from the bottom.

HEAT EXCHANGER

High-efficient rotary heat exchanger is available in two types:

- Condensing (aluminum) type - standard;
- Enthalpy type for hot and humid areas - optional.

DAMPERS

Integrated automatic external dampers with Belimo drives. Included in units starting from 1500.



FILTERS

Panel F7 class filters on both supply and exhaust.