

FORCE / FORCE MAX

CENTRIFUGAL FANS

Features


- Centrifugal fans.
- Wall surface or flush mounting.
- Centrifugal impeller with forwards curved blades ensures high pressure.
- Gravity backdraft damper for back flow prevention.
- Removable grille with dust filter.
- Modification with a grease filter (model Force...A) for use as a kitchen exhaust hood.
- Continuous operation.
- 5 years warranty.



Air flow:
up to 122 m³/h
34 l/s



Power:
from 16 W
SFP:
from 0.59 W/l/s



Noise level:
from 36 dBA


Options


Model	Force (Max) 100					
Option	S	T	ST	H	SH	IR
Pull-cord switch	•		•		•	
Timer		•	•	•	•	•
Humidity sensor				•	•	
Motion sensor						•

Timer


- Turn-off delay timer adjustable from 2 to 30 min.

Humidity sensor

- Humidity setpoint adjustable from 60 % up to 90 %.
- Turn-off delay adjustable from 2 up to 30 min.

Motion sensor


- Detection range from 1 up to 4 m.
- Detection angle up to 100°.
- Turn-off delay adjustable from 2 up to 30 min.

Overall dimensions


Dimensions [mm]	a	b	c	Ø D	e	f	g
Force (Max) 100	180	195	132	98	26	73	59

Technical data

Model	Force 100	Force Max 100
Voltage [V/Hz]	220-240/50	220-240/50
Power [W]	16	29
Air flow [m ³ /h (l/s)]	98 (27)	122 (34)
SFP [W/l/s]	0.59	0.86
Sound pressure level [dBA]*	36	38
RPM [min ⁻¹]	2250	2500

* Sound pressure level measured in free space at a distance of 3 meters from the fan.

Designation key

Force	Max	100	T	A
Model	High-powered motor	Spigot diameter	Option	Grease filter

Accessories

Duct system	Flexible air ducts	Grilles and hoods	Speed controllers	Clamps	Replaceable filters