

| | | | | | | |
|---|---|----|---------|---|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | Iso-RB 125 max | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -51,4 | A+ | -24,4 | C | -8,9 | F |
| Type of ventilation unit | Unidirectional | | | | | |
| Type of drive installed | Variable speed | | | | | |
| Type of heat recovery system | None | | | | | |
| Thermal efficiency of heat recovery, % | N/A | | | | | |
| Maximum flow rate, m ³ /h | 420 | | | | | |
| Electric power input, W | 88 | | | | | |
| Sound power level, dB(A) | 60 | | | | | |
| Reference flow rate, m ³ /s | 0,082 | | | | | |
| Reference pressure difference, Pa | 50 | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,296 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | N/A | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | http://www.blaubergventilatoren.de/ | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 157 | | 157 | | 157 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 5 536 | | 2 830 | | 1 280 | |