| Trade mark | BLAUBERG | | | | | |
|---|-------------------------------------|-----|---------|-----|-------|-----|
| Model | Civic EC LB 300-E S14 | | | | | |
| Specific energy consumption (SEC), kWh/(m².a) | Cold | | Average | | Warm | |
| | -75,5 | A+ | -39,4 | Α | -16,1 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | Variable speed | | | | | |
| Type of heat recovery system | Recuperative | | | | | |
| Thermal efficiency of heat recovery, % | 75 | | | | | |
| Maximum flow rate, m³/h | 320 | | | | | |
| Electric power input, W | 123 | | | | | |
| Sound power level, dB(A) | 42 | | | | | |
| Reference flow rate, m³/s | 0,063 | | | | | |
| Reference pressure difference, Pa | N/A | | | | | |
| Specific power input (SPI), W/(m³/h) | 0,243 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | 2,7 | | | | | |
| Maximum external leakage rates, % | 2,7 | | | | | |
| Internet address | https://www.blaubergventilatoren.de | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Co | old | Aver | age | Wa | ırm |
| | 72 | 24 | 18 | 37 | 14 | 12 |
| The annual heating saved (AHS), kWh primary energy/a | Co | old | Aver | age | Wa | ırm |
| | 8 4 | 90 | 4 3 | 40 | 1.9 | 963 |