

| | | | | | | |
|---|---|----|---------|---|-------|---|
| Trade mark | BLAUBERG | | | | | |
| Model | VENTO Ergo A50-1 S Pro1 | | | | | |
| Specific energy consumption (SEC), kWh/(m ² .a) | Cold | | Average | | Warm | |
| | -81,3 | A+ | -38,8 | A | -14,5 | E |
| Type of ventilation unit | Bidirectional | | | | | |
| Type of drive installed | 3-speed | | | | | |
| Type of heat recovery system | Regenerative | | | | | |
| Thermal efficiency of heat recovery, % | 80 | | | | | |
| Maximum flow rate, m ³ /h | 25 | | | | | |
| Electric power input, W | 7 | | | | | |
| Sound power level, dB(A) | 40 | | | | | |
| Reference flow rate, m ³ /s | 0,004 | | | | | |
| Reference pressure difference, Pa | N/A | | | | | |
| Specific power input (SPI), W/(m ³ /h) | 0,313 | | | | | |
| Control typology | Local demand control | | | | | |
| Maximum internal leakage rates, % | 2,7 | | | | | |
| Maximum external leakage rates, % | N/A | | | | | |
| Mixing rate of bidirectional units, % | 1 | | | | | |
| Airflow sensitivity at +20 Pa and -20 Pa | 0,4 | | | | | |
| The indoor/outdoor air tightness, m ³ /h | 0,5 | | | | | |
| Internet address | http://www.blaubergventilatoren.de/ | | | | | |
| The annual electricity consumption (AEC), kWh electricity/a | Cold | | Average | | Warm | |
| | 226 | | 226 | | 226 | |
| The annual heating saved (AHS), kWh primary energy/a | Cold | | Average | | Warm | |
| | 8 695 | | 4 445 | | 2 010 | |