


# FITTINGS

## FITTINGS FOR ROUND AIR DUCTS

### o Cross joint for round duct KS

- Made of white polymer coated steel (**KSM**) or galvanized steel (**KSZ**)
- Connection of round air ducts


| Model   | Ø D1 [mm] | Ø D2 [mm] | B (Length) [mm] |
|---------|-----------|-----------|-----------------|
| KSM 80  | 80        | 80        | 170             |
| KSM 100 | 100       | 100       | 190             |
| KSM 125 | 125       | 125       | 215             |
| KSM 150 | 150       | 150       | 240             |
| KSM 160 | 160       | 160       | 250             |
| KSM 200 | 200       | 200       | 300             |
| KSM 250 | 250       | 250       | 350             |
| KSM 315 | 315       | 315       | 415             |
| KSZ 80  | 80        | 80        | 170             |
| KSZ 100 | 100       | 100       | 190             |
| KSZ 125 | 125       | 125       | 215             |
| KSZ 150 | 150       | 150       | 240             |
| KSZ 160 | 160       | 160       | 250             |
| KSZ 200 | 200       | 200       | 300             |
| KSZ 250 | 250       | 250       | 350             |
| KSZ 315 | 315       | 315       | 415             |



### o T-connector for round air ducts TS-90°

- Made of white polymer coated steel (**TSM**) or galvanized steel (**TSZ**)
- Connection of round air ducts

| Model       | Ø D1 [mm] | Ø D2 [mm] | B (Length) [mm] |
|-------------|-----------|-----------|-----------------|
| TSM-90° 80  | 80        | 80        | 170             |
| TSM-90° 100 | 100       | 100       | 190             |
| TSM-90° 125 | 125       | 125       | 215             |
| TSM-90° 150 | 150       | 150       | 240             |
| TSM-90° 160 | 160       | 160       | 250             |
| TSM-90° 200 | 200       | 200       | 300             |
| TSM-90° 250 | 250       | 250       | 350             |
| TSM-90° 315 | 315       | 315       | 415             |
| TSZ-90° 80  | 80        | 80        | 170             |
| TSZ-90° 100 | 100       | 100       | 190             |
| TSZ-90° 125 | 125       | 125       | 215             |
| TSZ-90° 150 | 150       | 150       | 240             |
| TSZ-90° 160 | 160       | 160       | 250             |
| TSZ-90° 200 | 200       | 200       | 300             |
| TSZ-90° 250 | 250       | 250       | 350             |
| TSZ-90° 315 | 315       | 315       | 415             |



### o Backdraft damper for round ducts VRV

- Galvanized steel body and aluminium blades
- For prevention of back drafting in round air ducts
- Damper blades are opened by pressure and closed with a spring
- Connection to round air ducts by clamps

| Model   | Ø D [mm] | L (Length) [mm] |
|---------|----------|-----------------|
| VRV 100 | 99       | 80              |
| VRV 125 | 124      | 100             |
| VRV 150 | 149      | 115             |
| VRV 160 | 159      | 120             |
| VRV 200 | 199      | 145             |
| VRV 250 | 249      | 165             |
| VRV 315 | 314      | 190             |

